



2 No. SPECIFIED TREE TIES SECURELY FIXED TO STAKES AT 1300-1500mm ABOVE GROUND.

2 No. 50 x 50 x 2100 H.W. TIMBER STAKES TO BE DRIVEN 600-800mm INTO THE GROUND CLEAR OF THE ROOTBALL.

100mm DIAMETER FLEXI. AGI. PIPE WRAPPED AROUND BASE OF PLANTING HOLE WITH 2 No. DIAGONALLY OPPOSITE OPENINGS TO FINISH 50mm ABOVE MULCH.

100mm SPECIFIED MULCH TAPERED DOWN AROUND BASE OF TRUNK & SPREAD TO 600mm RADIUS OF TRUNK.

EXISTING SOIL & SUBSOIL TO BE EXCAVATED & CULTIVATED TO A MINIMUM OF TWICE THE WIDTH OF THE ROOTBALL AND EQUAL IN DEPTH. CONTAMINATED MATERIAL, ROAD BASE & PARTICLES GREATER THAN 75mm DIAMETER TO BE REMOVED.

TOP OF ROOTBALL TO FINISH LEVEL WITH SURROUNDING SOIL LEVEL.

UNDISTURBED SOIL/SUBSOIL.

NOTES:

- DRAWING TO BE READ IN CONJUNCTION WITH LANDSCAPE STANDARDS DOCUMENT, PLANT SCHEDULE & LANDSCAPE PLANS WHERE PROVIDED.
- TYPE B TYPICALLY APPLIES TO TREES IN LAWNS OR GARDEN BEDS.

CITY OF BALLARAT

No.	AMENDMENTS	DATE

Approved by: _____
Date: _____

**LANDSCAPE STANDARDS
ADVANCED TREE PLANTING
DETAIL - TYPE B**



SCALE:
NOT TO SCALE
SHEET 1 OF 1
DRAWING NO:
SD-L3