



REINSTATEMENT AREAS FOR PATH WIDTHS \leq 1.8m
 SCALE NTS (DIMENSION IN mm)

REINSTATEMENT AREA FOR PATH WIDTHS $>$ 1.8m
 SCALE NTS (DIMENSION IN mm)

NOTES

1. REINSTATED SURFACES SHALL BE FREE FROM LOW SPOTS THAT HOLD WATER.
2. THE FINISHED SURFACE LEVEL OF THE REINSTATEMENT TO BE FLUSH WITH THE EXISTING PAVEMENT LEVEL.
3. EXISTING ASPHALT SURFACES SHALL BE SAW CUT TO PROVIDE NEAT AND CLEAN EDGE FOR EXCAVATION.
4. PAVEMENT PROFILE OF FOOTPATH SHALL BE AS PER CITY OF BALLARAT STANDARD DRAWING SD-K2 OR AS DIRECTED BY ASSETS TEAM.
5. BACKFILL OF TRENCHES & AROUND STRUCTURES SHALL BE IN ACCORDANCE WITH IDM SD 310.
6. REINSTATEMENT AREA SHALL BE EXTENDED TO INCLUDE ANY DAMAGED SECTIONS DURING WORKS, OR AS DIRECTED BY ASSETS TEAM.
7. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.

CITY OF BALLARAT

01	PUBLISHED FIRST ISSUE	MAR 26	Approved by:	<h2 style="margin: 0;">REINSTATEMENT REQUIREMENTS - UTILITY WORKS IN ASPHALT PATHS</h2>	 CITY OF BALLARAT	SCALE: NOT TO SCALE
						SHEET: 1 OF 1
						DRAWING NO:
						SD-K6
No.	AMENDMENTS	DATE	Date: 24/04/2026			